




Partcode	Description	d	L	Angle (α)	Connection	Balancing (RPM)
L005	shrink fit tool holder	12	75	4°30'	BT 40A/B - BT 40/BP - CAT 40	24.000
L006	shrink fit tool holder	14	75	4°30'	SK 30 DIN 69871A/B - BT 30	24.000
L006	shrink fit tool holder	14	75	4°30'	SK 40 DIN 69871A/W/O FLANGE CUTS	24.000
L006	shrink fit tool holder	14	75	4°30'	SK 40 DIN 69871A/B	24.000
L006	shrink fit tool holder	14	75	4°30'	SK 40 DIN 69871/BP	24.000
L006	shrink fit tool holder	14	75	4°30'	SK 40 DIN 69871A/W/O FLANGE CUTS	24.000
L007	shrink fit tool holder	16	75	4°30'	BT 40A/B - BT 40/BP - CAT 40	24.000
L007	shrink fit tool holder	16	75	4°30'	SK 30 DIN 69871A/B - BT 30	24.000
L007	shrink fit tool holder	16	75	4°30'	SK 40 DIN 69871A/W/O FLANGE CUTS	24.000
L007	shrink fit tool holder	16	75	4°30'	SK 40 DIN 69871A/B	24.000
L007	shrink fit tool holder	16	75	4°30'	SK 40 DIN 69871/BP	24.000
L007	shrink fit tool holder	16	75	4°30'	SK 40 DIN 69871A/W/O FLANGE CUTS	24.000
L007	shrink fit tool holder	16	75	4°30'	BT 40A/B - BT 40/BP - CAT 40	24.000
L008	shrink fit tool holder	20	75	4°30'	SK 30 DIN 69871A/B - BT 30	24.000
L008	shrink fit tool holder	20	75	4°30'	SK 40 DIN 69871A/W/O FLANGE CUTS	24.000
L008	shrink fit tool holder	20	75	4°30'	SK 40 DIN 69871A/B	24.000
L008	shrink fit tool holder	20	75	4°30'	SK 40 DIN 69871/BP	24.000
L008	shrink fit tool holder	20	75	4°30'	SK 40 DIN 69871A/W/O FLANGE CUTS	24.000
L008	shrink fit tool holder	20	75	4°30'	BT 40A/B - BT 40/BP - CAT 40	24.000
L009	shrink fit tool holder	25	75	4°30'	SK 40 DIN 69871A/B	24.000
L009	shrink fit tool holder	25	75	4°30'	SK 40 DIN 69871/BP	24.000
L009	shrink fit tool holder	25	75	4°30'	SK 40 DIN 69871A/W/O FLANGE CUTS	24.000
L010	shrink fit tool holder	32	75	4°30'	BT 40A/B - BT 40/BP - CAT 40	24.000
L010	shrink fit tool holder	32	75	4°30'	SK 40 DIN 69871A/B	24.000

MANUFACTURING MATERIAL



TOOL HOLDERS SK/BT/CAT  
Shrink Fit Tool Holders

With run out specs up to ten times better than the collet chucks, the Shrink Fit Tool Holders are the most precise and the most reliable holding systems for high speed operations.



Partcode	Description	d	L	Angle (α)	Connection	Balancing (RPM)
L000	shrink fit tool holder	3	75	4°30'	SK 20 °C6G - SK 20 °E1TC	50.000
L000	shrink fit tool holder	3	75	4°30'	SK 25 °C6G	50.000
L001	shrink fit tool holder	4	75	4°30'	SK 20 °C6G - SK 20 °E1TC	50.000
L001	shrink fit tool holder	4	75	4°30'	SK 25 °C6G	50.000
L001	shrink fit tool holder	4	75	4°30'	SK 40 DIN 69871A/B - BT 30	24.000
L001	shrink fit tool holder	4	75	4°30'	SK 30 DIN 69871A/W/O FLANGE CUTS	24.000
L001	shrink fit tool holder	4	75	4°30'	SK 40 DIN 69871A/B	24.000
L001	shrink fit tool holder	4	75	4°30'	SK 40 DIN 69871/BP	24.000
L001	shrink fit tool holder	4	75	4°30'	SK 40 DIN 69871A/W/O FLANGE CUTS	24.000
L001	shrink fit tool holder	4	75	4°30'	SK 40 DIN 69871A/B	24.000
L001	shrink fit tool holder	4	75	4°30'	SK 40 DIN 69871/BP	24.000
L001	shrink fit tool holder	4	75	4°30'	SK 40 DIN 69871A/W/O FLANGE CUTS	24.000
L002	shrink fit tool holder	6	75	4°30'	BT 40A/B - BT 40/BP - CAT 40	24.000
L002	shrink fit tool holder	6	75	4°30'	SK 30 DIN 69871A/B - BT 30	24.000
L002	shrink fit tool holder	6	75	4°30'	SK 30 DIN 69871A/W/O FLANGE CUTS	24.000
L002	shrink fit tool holder	6	75	4°30'	SK 40 DIN 69871A/B	24.000
L002	shrink fit tool holder	6	75	4°30'	SK 40 DIN 69871/BP	24.000
L002	shrink fit tool holder	6	75	4°30'	SK 40 DIN 69871A/W/O FLANGE CUTS	24.000
L002	shrink fit tool holder	6	75	4°30'	SK 40 DIN 69871A/B	24.000
L002	shrink fit tool holder	6	75	4°30'	SK 40 DIN 69871/BP	24.000
L002	shrink fit tool holder	6	75	4°30'	SK 40 DIN 69871A/W/O FLANGE CUTS	24.000
L002	shrink fit tool holder	6	75	4°30'	BT 40A/B - BT 40/BP - CAT 40	24.000
L003	shrink fit tool holder	8	75	4°30'	SK 30 DIN 69871A/B - BT 30	24.000
L003	shrink fit tool holder	8	75	4°30'	SK 30 DIN 69871A/W/O FLANGE CUTS	24.000
L003	shrink fit tool holder	8	75	4°30'	SK 40 DIN 69871A/B	24.000
L003	shrink fit tool holder	8	75	4°30'	SK 40 DIN 69871/BP	24.000
L003	shrink fit tool holder	8	75	4°30'	SK 40 DIN 69871A/W/O FLANGE CUTS	24.000
L003	shrink fit tool holder	8	75	4°30'	BT 40A/B - BT 40/BP - CAT 40	24.000
L004	shrink fit tool holder	10	75	4°30'	SK 30 DIN 69871A/B - BT 30	24.000
L004	shrink fit tool holder	10	75	4°30'	SK 30 DIN 69871A/W/O FLANGE CUTS	24.000
L004	shrink fit tool holder	10	75	4°30'	SK 40 DIN 69871A/B	24.000
L004	shrink fit tool holder	10	75	4°30'	SK 40 DIN 69871/BP	24.000
L004	shrink fit tool holder	10	75	4°30'	SK 40 DIN 69871A/W/O FLANGE CUTS	24.000
L004	shrink fit tool holder	10	75	4°30'	BT 40A/B - BT 40/BP - CAT 40	24.000
L005	shrink fit tool holder	12	75	4°30'	SK 30 DIN 69871A/B - BT 30	24.000
L005	shrink fit tool holder	12	75	4°30'	SK 30 DIN 69871A/W/O FLANGE CUTS	24.000
L005	shrink fit tool holder	12	75	4°30'	SK 40 DIN 69871A/B	24.000
L005	shrink fit tool holder	12	75	4°30'	SK 40 DIN 69871/BP	24.000
L005	shrink fit tool holder	12	75	4°30'	SK 40 DIN 69871A/W/O FLANGE CUTS	24.000
L005	shrink fit tool holder	12	75	4°30'	SK 40 DIN 69871A/B	24.000
L005	shrink fit tool holder	12	75	4°30'	SK 40 DIN 69871/BP	24.000
L005	shrink fit tool holder	12	75	4°30'	SK 40 DIN 69871A/W/O FLANGE CUTS	24.000

Part codes for available  
SK/BT/CAT CONNECTIONS\*

To configure your toolholder you need to choose one of the following connections first.



\*See page 69 for the complete list of DIN manufacturing codes.

